
MOD. PLUS
thermal printer



Code 829008

Very compact and easy to install. Made in a watertight box (humidity and water-proof), it can be used on trailed and self-propelled mixers.

Paper changing is carried out by opening the frontal panel. It is provided with a 40-column-print mechanism on thermal paper 57,5 mm wide.

FEATURES

Printing Method	<i>thermal</i>
Columns	<i>40</i>
Paper type	<i>thermal</i>
Paper width	<i>57,5 ± 0,5 mm</i>
Roll measure	<i>∅ 50 mm (MAX)</i>
Connection	<i>StarBus</i>
Connecting cable	<i>1 or 3 metres</i>
Dimensions	<i>180 x 180 x 120 mm</i>
Working temperature	<i>0°C ÷ 50°C</i>

```

R 01 MIX 1    TOT= 10.00  24/10/11 17:19
GROUP 01 HIGH COW  COWS 0100 100%
GROUP 02 DRY COWS  COWS 0050 100%
INGREDIENT  PLANNED  LOADED
01 WATER    0150    0000
02 OATS     0300    0000
03 COTTON   0450    0000
04 FLOUR    0600    0000
GROUP      PLANNED  UNLOADED
01 HIGH COW 1000    0000
02 DRY COWS 0500    0000
OPERATION END          24/10/11 17:19
DURATION OF OPERATION          00:00
  
```

Example with Mod. 1500